

Polymelt Applicator Machines

POLYMELT APPLICATORS

POLYMELT APPLICATORS

Polymelt machines have been designed exclusively for use with **TM198**, taking into account the size of job required and the environment in which the machines need to operate.

All machines are available on wheels and in enclosures for ease of use and transport.

Polymelt 50 A-I (ATEX & IECEx)

- Polymelt 50 ATEX Zone 2/22 holds 22kgs (50lbs) of TM198 material
- Recommended for use in potentially hazardous areas, thanks to the pressurized enclosure
- Housed in a rugged stainless steel transport case and supplied with a 15m (50ft) hose
- Features a pre-melt system for continuous application
- For countries that require IEC, the machine conforms to IECEx Zone 2 Type Approval
- Ready to apply TM198 within 45mins
- Various power configurations available



OXIFREE[®]
METAL PROTECTION

www.oxifree.com

Polymelt 50

- Our larger unit for non-hazardous applications
- Holds 22kgs (50lbs) of TM198
- Features a pre-melt system for continuous application
- Housed in a rugged aluminium transport case with 34ft/10m or 50ft/15m hose
- Ready to apply TM198 within 45mins



Polymelt 12

- Versatile and portable the Polymelt 12 has a capacity of 5.5kg (12lbs) of TM198
- Easy to transport for demonstrations or smaller projects (typically up to a 4" diameter flange assembly)
- Comes with a 3.6m/12ft hose
- Comes in a transport case/trolley on wheels for ease of use
- Ready to apply TM198 within 60mins



Polymelt SG1

- Small, portable handheld gun for maintenance inspection and touch ups
- Weighs only 1.2kg on its own and 4.5kg in its case
- Single power source and easily applied by just one operator
- Utilises TM198 pellets – taking 2 at a time



OXIFREE[®]
METAL PROTECTION

www.oxifree.com